

**TECHNICAL
SHEET**

PROTECT 05
semipermanent

PROTECT 05
SEMIPERMANENT COATING,
WATER BASE & MONOCOMPONENT

DESCRIPTION

Protect 05 is a semipermanent and monocomponent coating with water base and hardens by the relationship, with the humidity of the air.

It has very good adhesion to various surfaces without previous priming whenever it has some porosity.

It is mono-component so that increases the rentabilidd of the work.



APLICACIONES

- Application: interior and exterior.
- Wood, metal work, painted iron, concrete, granite, marble, facades, painted facades, etc.

PROPIERTIES

- Does not quarter
- Does not form blisters
- Is no need to sand to repaint
- Breathable
- Reapplicable
- Non graffiti
- Non stickers
- Self cleaning
- Non pollute

FEATURES

- | | |
|-------------------------------------|----------------------------|
| ▪ Finished: | Satin |
| ▪ Performance approximated by hand: | 10-12 m ² / kg |
| ▪ Dry to the touch | (20 C° HR:60 %) 60 minutes |
| ▪ Total dry: | 24 hours |
| ▪ Total hardening: | 5 days |
| ▪ Colours: | Transparent |

PREPARATION OF THE SURFACE

- The support has to be exempt of strange products, oxides or residues.
- Apply on surfaces well desengrasadas, powder-free and dry.
- If it was cleaned with pressurized water expected to be dry.
- If he was cleaned with chemicals restore PH between 6-8.

INSTRUCTIONS FOR USE

- Do not apply the product with high temperatures.
- Do not apply with humidities above 85%, or at temperatures below 5 ° C or above 35 ° C.
- You can apply to brush, roller, paint gun.
- Is applied to give a thin layer on the support to be protected

GENERAL INFORMATION

- The data outlined here are based on our current knowledge, testing laboratory and in specific circumstances and objective judgments obtained in the practical use.
- Due to the impossibility of establishing an appropriate to each nature and State description, taking into account the surface to protect, it is impossible to ensure total reproducibility in each case.

PRESENTATION

- 4 kg, 1kg, 500gr.

EXPIRATION

- Recommended storage no more than 12 months, taking into account the date of manufacture defined in the original container.
- Keep always the packaging original, perfectly closed and covered.
- Temperature of storage between 15-20 ° C.