



RP-RC430V

TRAY SEALING MACHINE WITH VACUUM AND GAS (MAP) AND SKIN (OPTION)

TECHNICAL FEATURES

DIMENSIONS _____	630 x 750/970* x 1680 mm
NET WEIGHT _____	170 Kg
VOLTAGE (to choose)** _____	II, 230v. 50/60Hz ; III, 400v. 50/60HZ.
POWER _____	2,5/3,5 kW.
PANEL TYPE _____	Screen with 10 programs
MAX. DIMENSIONS OF TRAY (without die cut) _____	420 x 280 mm
MAX. DEEPTH OF TRAY _____	100 mm
PUMP _____	21/40 m3/h. (option)
MAX.WIDTH AND DIAMETRE OF FILM _____	420 mm / 320 mm Ø
GAS FEEDING PRESSURE _____	Max 2,5 bars
PNEUMTAIC FEEDING PRESSURE _____	6 bars – 6 NL/C

* with film collector.
** Other voltages available on request.

MAIN FEATURES

- Semi-automatic machine for the packaging of product in trays.
- Hygienic and waterproof sealing of all products.
- Significantly extends the life of packaged products and gives an optimal presentation.
- Electronic control to set:
 - Temperature, sealing time, vacuum percentage, gas percentage, extra vacuum time, and others.
- Can be equipped with upper mould with die cut or without.
- Change of upper mould and mould easy and fast.
- Automatic start of the cycle at the insertion of the mould box and acoustic and luminous signal at the end of the cycle.
- Automatic film dragging at the entrance of the mould box. Optionally can be equipped with motor that reels the cut of the film that remains after the cycle.
- The machine is provided in a standard way prepared for sealing or vacuuming with gas (MAP). Can choose the mode directly on the screen. Optionally the machine can equip also with the SKIN mode.